



FLIR Ranger[®] R20SS

Solid State, Electronic Scanning, Long Range
Surveillance Radar

The Ranger[®] R20SS is a ground-based surveillance radar that provides fast detection and accurate target location within a 30 kilometer range. Featuring advanced electronic scanning, the Ranger R20SS can cover an entire 90-degree area twice per second with low false alarm rates. With both man-portable and vehicle mounted options, the Ranger R20SS is ideal for military vehicle applications.

Accurate target location

The Ranger R20SS utilizes advanced tracking algorithms which enable fast detection and track initiation, resulting in highly accurate target location with a low false alarm rate. And by operating in the X-band, the Ranger R20SS is minimally affected by adverse weather or precipitation.

Next-generation track and scan capabilities

The Ranger R20SS provides fast 90-degree coverage using enhanced “track while scan” capabilities that cover an entire 90-degree area twice per second. When deployed with an optional pan/tilt device, the Ranger R20SS can provide 360-degree coverage.

Low SWaP applications

R20SS radar performs over land and over water allowing the use of a single radar for both applications. The result is lower ILS costs and reduced training and spare requirements. The low SWaP requirements minimize infrastructure costs in coastal applications. Its low weight and easy implementation make it an ideal candidate for military vehicle applications and deployable in a man-portable configuration. As with the entire line of Ranger ground surveillance radars, the Ranger R20SS provides highly reliable system performance and 24/7 persistent surveillance, both within and beyond the fence.



Critical Infrastructure Protection



Mobile Border Surveillance



Coastal Surveillance

Specifications

Target Types Moving	> 0.1 m/s min Vehicles, personnel, rubber rafts, boats
Target Velocity	0.1 to 44 m/s
Number of tracks	over 500
Scan Rate	2 Hz (90 degree sector)
Coverage	90° in sector mode 360° in scan mode (with optional pan/tilt device)
Elevation Control	Yes with optional Pan/Tilt
Input Power	21-42 VDC, 24 nominal
Communications	Ethernet, wireless, fiber
XML	Yes (ICD-0100 compliant)
Mask Zone(s)	Unlimited polygons
Dimensions	29.6" h x 14.7" w x 6.0" d, no pan/tilt
Weight	38 lbs (17.3 kg), no pan/tilt
Power Consumption	245 watts (standard version) 170 watts (low-power version)
Operating Range	20 – 30,000 m
Detection Range	up to 12,000 m, personnel walking (1 m ² RCS) up to 12,000 m, rubber raft (1 m ² RCS, sea state 3) up to 20,000 m, patrol vessel (10 m ² RCS, sea state 4) up to 28,000 m, vehicles, large vessels
Temperature	-30° to +60°C (operating) -40° to +70°C (storage)
Humidity	Up to 100%,
Weather Sealing	IP 67 Rating
Altitude	Up to 15 000 ft (operating and storage)
Mil Spec	Complies with MIL-STD-810 and MIL-STD-461

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. ©2015 FLIR Systems, Inc. Specifications are subject to change. Check website: www.flir.com/surveillance

FEATURES

- Optional pan/tilt device offers 360-degree coverage
- Low SWaP requirements minimize ILS costs, including reduced training and spare requirements
- Persistent wide-area surface surveillance 24/7
- Mil-spec design and qualification
- Easy sensor integration
- Performs over land and over water
- Low lifecycle cost

APPLICATIONS

- Border Security
- Coastal Surveillance
- Force Protection
- Industrial Facility
- Critical Infrastructure Security
- Air & Sea Ports
- Vehicle & Man-Portable Capabilities

NASHUA
FLIR Systems, Inc.
9 Townsend West
Nashua, NH 03063
USA
PH: +1 866.477.3687

PORTLAND
Corporate Headquarters
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 866.477.3687

EUROPE
FLIR Systems
Luxemburgstraat 2
2321 Meer
Belgium
PH: +32 (0) 3665 5100

CANADA
FLIR Systems, Ltd.
120-3440 av Francis-
Hughes, Laval, Québec,
H7L 5A9
Canada
PH: +1 800.613.0507

www.flir.com/surveillance
NASDAQ: FLIR

SWEDEN
FLIR Systems AB
Antennvägen 6,
PO Box 7376
SE-187 66 Täby
Sweden
PH: +46 (0)8 753 25 00

UK
FLIR Systems UK
2 Kings Hill Avenue
Kings Hill
West Malling - Kent
ME19 4AQ
United Kingdom
PH: +44 (0)1732 220 011

LATIN AMERICA
FLIR Systems Brasil
Av. Antonio Bardella, 320
Sorocaba, SP 18052-852
Brasil
TEL: +55 15 3238 7080

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2015 FLIR Systems, Inc. All rights reserved. (Rev. 1, 12/02/15)