



HIGH-RESOLUTION PERIMETER INTRUSION DETECTION

FLIR Ranger® R3

The Ranger® R3 is a high-resolution radar that accurately detects personnel and vehicles at a range of up to 2,800 meters in virtually any climate, weather, or lighting condition to provide 24/7 security. Able to scan 360° every second to monitor more than 24 square kilometers (9.6 square miles), it can be integrated in an overlapping array with a variety of other radar and EO/IR units to conform to terrain profiles and protect larger areas such as borders.

Operating in the Ka-band, this radar is compact and highly portable. In addition to border surveillance, R3 is ideal for force protection and securing airports, seaports, and critical infrastructure. R3 provides fast and accurate detection of up to 128 threats simultaneously. For a more efficient, cost-effective solution, integrate R3 with pan-tilt-zoom (PTZ) cameras to identify and assess threats.

FEATURES

MULTIPLE SECURITY APPLICATIONS

Whether securing airports, seaports, borders, critical infrastructure, or for force protection, FLIR radars provide an ideal wide-area surveillance solution.

LOW FALSE ALARM RATE

Accuracy, ease of operation, and the lowest false alarm rate in the industry, separates FLIR Ranger radars from the competition.

NETWORKED PROTECTION

Integrate R3 with Ranger R1 and R2 radars as well as DefendIR cameras to secure areas inside and outside perimeters.

FAST, ACCURATE THREAT DETECTION

R3 quickly detects up to 128 threats simultaneously while accurately displaying each target's location.

RELIABLE OPERATION & EASY INTEGRATION

High availability rate saves on costs for spare systems or repairs, and it requires only one cable and four bolts for integration.

APPLICATIONS

SECURE BORDERS

MONITOR PORTS

GUARD INDUSTRIAL FACILITIES

FORCE PROTECTION

DEFEND PUBLIC INFRASTRUCTURE

SPECIFICATIONS

Ranger R3

Target Types	Moving vehicles and personnel
Operating Range	5 m – 2800 m
Resolution	0.3 m (range) x 1° (azimuth)
Detection Range	5 m – > 500 m, Crawler 5 m – 1900 m, Personnel 5 m – 2500 m, Vehicles
Range Accuracy	2m typical
Target Speed	0.1 m/s or greater
Target Travel Direction	No limitations
Coverage Area	24 km ² (9.6 mi ²)
Frequency	Ka-Band
Scan Rate	1 revolution per second
Azimuth Beamwidth	1° (2-way)
Elevation Beamwidth	6° (2-way)
Elevation Control	Up: 2.5°; down 10° (fixed settings)
False Alarm Rate	1 per 24 hours
Input Power	20 – 32 VDC
Radiated Power	Safe for human exposure
Outputs	Ethernet; Intruder location (latitude/longitude, range/bearing, intruder course/velocity, signal quality)
XML	Yes
RF Transmission Masks	2 configurable “no transmit” sectors 1° resolution
Size	14.4” height x 18.25” diameter (364 x 461mm)
Weight	29 lbs (13.1 Kg)
Temperature	-30°C to +65°C
Weather Sealing	IP66 rating
Humidity	Up to 100%



AMERICAS

FLIR Systems, Inc.
Corporate Headquarters
27700 SW Parkway Ave
Wilsonville OR 97070
Office: +1 877.773.3547

FLIR Systems, Inc.
DC Headquarters
1201 S. Joyce Street
Suite C006
Arlington, VA 22202
Office: +1 703.682.3400

EUROPE

FLIR Systems
2 Kings Hill Avenue - Kings Hill
West Malling, Kent ME19 4AQ
United Kingdom
Office: +44 (0)1732 220 011
Fax: +44 (0)1732 843 707

FLIR Systems AB
Antennvägen 6,
PO Box 737
SE-187 66 Täby
Sweden
Office: +46 (0)8 753 25 00

MIDDLE EAST

FLIR Systems B.V. - Abu Dhabi
Wadi Al Fey St.
Building 60, Office # 302
New Ministries Exit / Khalifa Park Area
Abu Dhabi, U.A.E.
Office: +971 2 666 1561
e-Fax: +1 503 914 1591

FLIR Systems Saudi Arabia
Office 127, First Floor
Akaria Plaza Building, Olaya Street
Riyadh, 11481, Saudi Arabia
Office: +966 11 464 5323
Fax: +966 11 464 0438

ASIA

FLIR Systems Japan K.K.
Meguro Tokyu Bldg. 5F,
2-13-17
Kami-Osaki, Shinagawa-ku.
Tokyo, 141-0021, Japan
Office: +81-3-6721-6648

For More Information contact
surveillance_sales@flir.com

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. 01/02/19

18-2742-SUR-LND-Ranger R3-Specsheet LTR



The World's Sixth Sense®