



## DUAL MODE, PERIMETER SURVEILLANCE RADAR

# FLIR Ranger® R3D

The Ranger R3D is a dual mode, ground surveillance radar designed to provide efficient, 24/7 persistent surveillance, both within and beyond the fence. Operating in the Ka-band, the Ranger R3D leverages the resolution and accuracy of advanced FMCW technology and the extended range and terrain adaptability of Doppler in a single, compact, and lightweight package. Ruggedized for permanent, all-weather installations and mobile, stop-and-scan operations, its low minimum detection velocity (MDV) detects slow-moving threats such as walkers and crawlers.

A COTS unit for detecting and tracking surface movement, R3D provides wide area detection when used as a cueing device. Operators can be confident of up to 128 threats at a time due to low false alarm rates. Network with other FLIR radars to create an overlapping array that protects larger areas such as borders, ports, airports, and military bases. Target information output includes ID, location, range, bearing, latitude, longitude, confidence level, heading, speed, and time.

### FEATURES

#### FMCW DOPPLER CAPABILITY

Ranger R3D Doppler provides extended range coverage in almost any terrain. Overcome blind target ranges/velocities by switching to Fast Scan/FMCW.

#### DUAL-MODE CAPABILITY

Switch between Fast Scan and Doppler depending on terrain and recognition requirements. Enhanced performance supports both radial and tangential detection.

#### INTEGRATED PROTECTION

Network multiple FLIR radars and EO/IR imagers with FLIR command and control to form a single powerful, integrated surveillance system.

#### FAST, ACCURATE THREAT DETECTION

R3D quickly detects up to 128 threats simultaneously while accurately displaying each target's location.

#### RUGGEDIZED FOR RIGOROUS DUTY

Designed for permanent, all-weather installations and mobile, stop-and-scan operations, R3D can detect pedestrians, crawlers, and vehicles in virtually any environment.

### APPLICATIONS

BORDER SECURITY

INDUSTRIAL FACILITY SECURITY

MONITOR PORTS, AIRPORTS, & MILITARY BASES

CRITICAL INFRASTRUCTURE PROTECTION

FORCE PROTECTION

## SPECIFICATIONS

R3D	
Target Types	Moving, Less than 0.1m/s minimum for vehicles and personnel
Target Velocity	0.1 to 50 m/s
Communications	Ethernet, wireless, fiber
XML	Yes (ICD-0100 compliant)
Target Information	Includes: ID; location: range & bearing; latitude & longitude; Confidence level; Heading; Speed; Time
Command & Control	
Scan Rate	3 to 60 rpm, continuous or sector
Elevation Coverage	6°, 12° option
Elevation Control	Up: 2°; Down: 5° (fixed settings)
Input Power	20 to 32 VDC, 24 nominal
Radiated Power	Safe for human exposure
False Alarm Rate	< 1 per 24 hours (Fast Scan)
Mask Zone(s)	One angular detection zone (Doppler) Two selectable angular detection zones (Fast Scan) One selectable angular detection zone (Doppler) Unlimited polygon detection zones
Environmental	
Network	Up to 8 per server; total unlimited
Dimensions	14.7" h x 18.3" diameter
Weight	29 lbs (14kg)
Power Consumption	40 watts
Operating Range	5 – 6,500 m
Detection Range	5 – 3,500 m, personnel walking 5 – 6,500 m, vehicles and watercrafts
Coverage Area	133 km <sup>2</sup> (53 mi <sup>2</sup> )
Temperature	-30° to +65°C (operating) -40° to +70°C (storage)
Humidity	50% to 95%, non-condensing (60°C max)
Altitude	Up to 15 000 ft (operating and storage)
Wind	Up to 140 km/hr
Weather Sealing	IP 65 rating
Protocol	ICD-0100

## DETECTION PERFORMANCE

	Fast Scan (no Doppler)	Fast	Doppler Intermediate	Long Range
Instrument Range	2,800 m	6,500 m	6,500 m	6,500 m
Detection Pedestrian	1,900 m	2,500 m	3,000 m	3,500 m
Detection Light Vehicle	2,500 m	4,300 m	5,000 m	6,000 m



### AMERICAS

FLIR Systems, Inc.  
Corporate Headquarters  
27700 SW Parkway Ave  
Wilsonville OR 97070  
Office: +1 877.773.3547

FLIR Systems, Inc.  
DC Headquarters  
1201 S. Joyce Street  
Suite C006  
Arlington, VA 22202  
Office: +1 703.682.3400

### EUROPE

FLIR Systems  
2 Kings Hill Avenue - Kings Hill  
West Malling, Kent ME19 4AQ  
United Kingdom  
Office: +44 (0)1732 220 011  
Fax: +44 (0)1732 843 707

FLIR Systems AB  
Antennvägen 6,  
PO Box 737  
SE-187 66 Täby  
Sweden  
Office: +46 (0)8 753 25 00

### MIDDLE EAST

FLIR Systems B.V. - Abu Dhabi  
Wadi Al Fey St.  
Building 60, Office # 302  
New Ministries Exit / Khalifa Park Area  
Abu Dhabi, U.A.E.  
Office: +971 2 666 1561  
e-Fax: +1 503 914 1591

FLIR Systems Saudi Arabia  
Office 127, First Floor  
Akaria Plaza Building, Olaya Street  
Riyadh, 11481, Saudi Arabia  
Office: +966 11 464 5323  
Fax: +966 11 464 0438

### ASIA

FLIR Systems Japan K.K.  
Meguro Tokyu Bldg. 5F,  
2-13-17  
Kami-Osaki, Shinagawa-ku.  
Tokyo, 141-0021, Japan  
Office: +81-3-6721-6648

For More Information contact  
surveillance\_sales@flir.com

www.flir.com  
NASDAQ: FLIR

Equipment described herein pertains to a Canadian origin product that is controlled as dual-use by the Canadian government. When in the United States or possessed by a US person, it may be subject to US Jurisdictions, which may require authorization to re-transfer to a foreign person. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. 07/12/19

18-2743-SUR-LND-Ranger R3D-  
Specsheet LTR



The World's Sixth Sense®