



DUAL MODE, PERIMETER SURVEILLANCE RADAR

FLIR Ranger® R5D

The Ranger® R5D is a dual mode, ground surveillance radar designed specifically for the environmental conditions common to the Middle East region. As a dual mode radar, the Ranger R5D uses FMCW modulation and can be operated in either Fast Scan or Doppler mode with a Fast Scan range up to 5km. Low minimum detection velocity (MDV), high resolution, and advanced tracking algorithms result in low false alarm rates.

Operating in the Ka-band, this radar is compact and highly portable. It scans 360° every second, 24/7, monitoring large areas in most climates in real time. Easily network other FLIR radars and EO/IR images for slew-to-cue capabilities. Ideal for desert environments, border security, and force protection, R5D provides fast and accurate detection of up to 128 threats simultaneously.

FEATURES

FMCW DOPPLER CAPABILITY

Ranger R5D Doppler provides extended range coverage in almost any terrain. Overcome blind target ranges/velocities by switching to Fast Scan/FMCW.

DUAL-MODE FLEXIBILITY

Both modes share one antenna and detect tangential movement. Scan rate, RF bandwidth, and PRFs are optimized per selected mode.

INTEGRATED PROTECTION

Network multiple FLIR radars and EO/IR imagers with FLIR command and control to form a single powerful, integrated surveillance system.

FAST, ACCURATE THREAT DETECTION

R5D quickly detects up to 128 threats simultaneously while accurately displaying each target's location.

RELIABLE OPERATION & EASY INTEGRATION

High availability rate saves on costs for spare systems or repairs, and it requires only one cable and four bolts for integration.

APPLICATIONS

DESERT ENVIRONMENTS

SECURE BORDERS

FORCE PROTECTION

INDUSTRIAL FACILITY SECURITY

CRITICAL INFRASTRUCTURE SECURITY

MONITOR PORTS, AIRPORTS, & MILITARY BASES


SPECIFICATIONS

R5D	
Target Types	Moving, Less than 0.1m/s minimum for vehicles and personnel
Target Velocity	0.1 to 50 m/s
Communications	Ethernet, wireless, fiber
XML	Yes (ICD-0100 compliant)
Target Information	Includes: ID; location: range & bearing; latitude & longitude; Confidence level; Heading; Speed; Time
Command & Control	
Scan Rate	3 to 60 rpm, continuous or sector
Elevation Coverage	4°
Elevation Control	Up: 2°; Down: 5° (fixed settings)
Input Power	20 to 32 VDC, 24 nominal
Radiated Power	Safe for human exposure
False Alarm Rate	< 1 per 24 hours (Fast Scan)
Mask Zone(s)	One angular detection zone (Doppler) Two selectable angular detection zones (Fast Scan) Unlimited polygon detection zones
Environmental	
Network	Up to 8 per server; total unlimited
Dimensions	22.5" h x 21.3" diameter
Weight	37 lbs (17kg)
Power Consumption	40 watts
Operating Range	5 – 10 000 m
Detection Range	5 – 5,500 m, personnel walking 5 – 9,400 m, vehicles and watercrafts
Coverage Area	346 km ² (135 mi ²)
Temperature	-30° to +65°C (operating) -40° to +70°C (storage)
Humidity	50% to 95%, non-condensing (60°C max)
Altitude	Up to 15,000 ft (operating and storage)
Wind	Up to 140 km/hr
Weather Sealing	IP 65 rating
Protocol	ICD-0100

DETECTION PERFORMANCE

	Fast Scan (no Doppler)	Fast	Doppler Intermediate	Long Range
Instrument Range	5,600 m	10,500 m	10,500 m	10,500 m
Detection Pedestrian	3,000 m	4,000 m	4,600 m	5,500 m
Detection Light Vehicle	5,000 m	6,800 m	8,000 m	9,400 m

*Note: In Doppler long mode, scan angle is limited to 180°



AMERICAS

FLIR Systems, Inc.
Corporate Headquarters
27700 SW Parkway Ave
Wilsonville OR 97070
Office: +1 877.773.3547

FLIR Systems, Inc.
DC Headquarters
1201 S. Joyce Street
Suite C006
Arlington, VA 22202
Office: +1 703.682.3400

EUROPE

FLIR Systems
2 Kings Hill Avenue - Kings Hill
West Malling, Kent ME19 4AQ
United Kingdom
Office: +44 (0)1732 220 011
Fax: +44 (0)1732 843 707

FLIR Systems AB
Antennvägen 6,
PO Box 737
SE-187 66 Täby
Sweden
Office: +46 (0)8 753 25 00

MIDDLE EAST

FLIR Systems B.V. - Abu Dhabi
Wadi Al Fey St.
Building 60, Office # 302
New Ministries Exit / Khalifa Park Area
Abu Dhabi, U.A.E.
Office: +971 2 666 1561
e-Fax: +1 503 914 1591

FLIR Systems Saudi Arabia
Office 127, First Floor
Akaria Plaza Building, Olaya Street
Riyadh, 11481, Saudi Arabia
Office: +966 11 464 5323
Fax: +966 11 464 0438

ASIA

FLIR Systems Japan K.K.
Meguro Tokyu Bldg. 5F,
2-13-17
Kami-Osaki, Shinagawa-ku.
Tokyo, 141-0021, Japan
Office: +81-3-6721-6648

For More Information contact
surveillance_sales@flir.com

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. 01/02/19

18-2745-SUR-LND-Ranger R5D-Specsheet LTR



The World's Sixth Sense®